

MID-SIZE WALK-BEHIND MOWERS 91CM SIDE DISCHARGE • FLOATING DECK

KING TO THE T

ORC

With the Second

MID-SIZE WALK-BEHIND MOWERS • FLOATING DECK

- PREVENT IMPACT DAMAGE with TURBO FORCE 7-gauge steel deck and welded bull-nose bumper.
- ENHANCE DURABILITY with robust cast iron spindle housings with maintenance-free sealed bearings.
- FINE-TUNE THE CUT for different conditions or seasons with the patented adjustable baffle.
- MAXIMIZE PERFORMANCE with commercially proven heavy-duty drive system.



MID-SIZE	30070 - GEAR	30071 - HYDRO
CUTTING WIDTH	91 cm	91 cm
ENGINE	Kawasaki, 4-cycle, 603 cc, FS481V, Air-cooled	Kawasaki, 4-cycle, 603 cc, FS481V, Air-cooled
STARTER	Recoil	Recoil
DRIVE SYSTEM	Peerless® 5-speed, with reverse	Twin Hydro-gear® pumps with Parker wheel motors
DECK TYPE	TURBO FORCE® Side Discharge, Recycler	TURBO FORCE® Side Discharge, Recycler
нос	25 - 114mm	25 - 114mm
SPEED	Forward: 0 - 7.5 km/h; Reverse: 3.7 km/h	Forward: 0 – 8.0 km/h; Reverse: 3.2 km/h
FUEL/CAPACITY	Petrol / 18 litres	Petrol / 18 litres
WEIGHT	267 kg	303 kg

= Enhanced or step-up feature



30070 – T-BAR GEAR CONTROL

Exclusive 'T-Bar' control system is easy to learn and operate. Peerless 5-speed gear drive system with reverse. Hour meter fitted as standard.



30071 – T2 HYDRO CONTROL

Twin lever 'T2' control system with independent choke and throttle controls provide precise starting for operational control. Twin Hydrogear pumps ensure smooth and easy operation with fast 8.0km/h forward speed. Hour meter fitted as standard.



RUBBER DISCHARGE CHUTE

Flexes to allow close trimming without damaging the chute or landscaping structures.



TURBO FORCE® DECK Provides strength and durability with its' heavy-duty welded 7-guage steel construction. A 13mm wear guard on the trim side of the deck and bull-nose bumper have been added for extra strength.



COMMERCIAL-GRADE ENGINES

Delivers many hours of troublefree life. Twin cylinder design runs smooth and delivers excellent load response.



FLAT-FREE CASTER TYRES Eliminate time-consuming flats so mowers can spend more time in the field and less time in the shop.

toro.com

Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801 Fax: (1) 952 887 8258

Printed in U.S.A. ©2016 The Toro Company. All Rights Reserved. 200-6471



facebook.com twitter.com/TheToroCompany youtube.com/ToroCompanyEurope



