

**TORO**

Count on it.

## Topdresser 1800 & 2500



**TORO** Count on it.

# Spread the word.

## 1800

- 502 litre (18 cu ft.) capacity
- 13 km/h (8 mph) topdressing speed

## 2500

- 698 litre (25 cu. ft.) capacity

When superintendents need a topdresser that is as dependable as it is productive, they count on the Toro® Topdresser 1800 and 2500. Both models feature a large hopper to get your turf covered quickly. Choose between a vehicle-mounted model or a towable model to get the even application you need — light to heavy.



## Count on Performance

### The ultimate gatekeeper.

The Topdresser's spring-loaded gate control mechanism holds the gate firmly in position, yet allows rocks and debris to pass without jamming.





## Precise and productive.

Every Toro Topdresser is built for speed and performance. The 1800 has an 18 cu. ft. (502 liter) hopper that mounts to the back of a Toro Workman® or other utility vehicle. The 2500 holds 25 cu. ft. (698 liters) of material and is towed behind a utility vehicle. Both units have a fast topdressing speed of 8 mph (13 km/h), remote controls, and a high-speed brush for precision application of both wet and dry materials. And the application belts have a seamless, v-pattern design for consistent performance, even with fine broadcast rates. The 2500's four drive wheels are mounted on twin oscillating axles to keep the Topdresser level on uneven terrain.



Four wide tires on the 2500 reduce ground contact pressure to protect turf without sacrificing maneuverability.



The 2500's hydraulic drive system reduces maintenance that is inherent with mechanical drive mechanisms.



Choose between the utility vehicle-mounted 1800 or the hydraulically-driven 2500 to meet your topdressing needs.

## Specifications for Topdresser 1800 & 2500

	1800	2500
<b>General</b>		
<i>Drive:</i>	Remote hydraulic to utility vehicle	Self-contained, ground-driven hydraulic system, no hoses connected to tow vehicle
<i>Brakes:</i>	Not applicable	Electro/hydraulic
<i>Wheels &amp; Tires:</i>	Not applicable	(4) 18 x 10.5-8, 4-ply, high-floatation turf tires on oscillating axle sets
<i>Topdressing Speed:</i>	Up to 13 km/h (8 mph)	Up to 13 km/h (8 mph)
<i>Transport Speed:</i>	Up to 19 km/h (12 mph)	Up to 19 km/h (12 mph)
<i>Controls:</i>	Hydraulic engage/disengage lever from operator console	12 volt on/off switch at operator position to engage conveyor and brush
<b>Hopper</b>		
<i>Capacity:</i>	502 litre (18 cu. ft.)	698 litre (25 cu. ft.)
<i>Conveyor Belt:</i>	Continuous 152 cm (60") wide belt, polyester mono-filament interwoven material w/gray PVC V-pattern traction surface	
<i>Metering Gate:</i>	Infinitely variable from closed to 9 cm (3.5") opening for light to heavy applications, flexible edge and spring release	
<b>Dimensions</b>		
<i>Length:</i>	132 cm (52")	248 cm (97.5")
<i>Width:</i>	184 cm (72.5")	184 cm (72.5")
<i>Height:</i>	109 cm (43")	109 cm (43")
<i>Warranty:</i>	Two-year limited	Two-year limited

### TORO® PROFESSIONAL SERVICES

**Toro Financing** Many flexible financing options are available to meet your specific operational requirements.

**Toro Genuine Parts** Keep the productivity and performance of your equipment at its peak by using genuine Toro replacement parts. Find and identify your replacement parts online at [www.Toro.com/partsviewer](http://www.Toro.com/partsviewer).

**Toro Training** Toro Technical Service Schools are available from your local distributor. Explore the training and customer care areas of [Toro.com](http://Toro.com) and [ToroNSN.com](http://ToroNSN.com) for readily available on-line education and training materials.

**Toro Controller Repair** Provides irrigation controller boards ready for immediate board exchange to assure that downtime is minimal and your turf stays protected. Toro is the choice for reliability. +1 909 785 3630

**Toro NSN®** An industry-first support network that provides reliable, around-the-clock irrigation central control system trouble-shooting and operation assistance. For assistance please contact:

Canada / Mexico / Latin America +1 325 673 8762

Europe / Middle East / Africa +32 (0) 14 56 29 33

Australia / Asia-Pacific +61 7 3268 2154

Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary.

©2004 The Toro Company, 8111 Lyndale Ave. S., Bloomington, MN 55420-1196

GB Part No. 200-2522. Printed in U.S.A.

[www.toro.com](http://www.toro.com)



**Count on it.**