

## Experience the completely new R50-11 Greens Roller.

Building on our long history of industry leading design and innovation, Tru-Turf has incorporated more world firsts, making the industry leading roller even better!

Driven by a flexible, full width contour following drive roller and equipped with Tru-Turf's patented triple offset smoothing rollers, following contours is a breeze. Combine this with overlapping roller heads and our innovative new self cleaning smoothing roller system and you achieve a true, smooth 50" (1270mm) wide roll on the most contoured greens without leaving gaps, grass clippings or line crease marks.

Always evolving, we have incorporated a new quick release design allowing for a fast, safe and tool free transition between brushing, spiking or slicing attachments. This allows you to spend less time in the workshop and more time on the greens, saving you time and money.

While other greens rolling machines rely on weight to heavily compress the playing surface, Tru-Turf lightweight rollers create fast, true surfaces, without compacting the soil beneath, resulting in healthier greens.

Experience the Tru-Turf advantage today. Contact your local dealer and see the results for yourself.





## CHOOSE THE OPTIONS THAT SUIT YOUR NEEDS

The R50-11 comes standard with our hassle free, self cleaning, self adjusting, smoothing roller nodules.

Look no further than our innovative range of optional attachments that can help increase productivity and provide great results through design, not weight.



Changing attachments has never been so easy. Simply remove the quick release safety pin & switch out the attachment.









## **R50-11 Specifications**

Engine	
Туре	Honda 2:1
Horsepower	6.5hp (4.85 kw)
Lighting Coil	Built into engine
Engine Cover	Fully enclosed
Transmission	
Manufacturer	Eaton
Model	Hydrostatic Series, 11
Oil Capacity	
Engine	1.05qts (1L) + Filter
Transmission	6qts (6.84L) + Filter
Cooling	
Engine	Air cooled
Transmission	8 blade cooling fan
Drive Train	1/2" duplex chain, self-adjusting
Drive Roller	Rubber coated, non-stick.
	Flexible, contour following
Direction Control	Ergonomically positioned foot pedals
Speed Control	Progressive foot pedal movement, down/
	up Dampeners for smooth stopping
Operating Speed	0-9 mph (0-15kph)
Steering	Joystick - Light load, directly connected to
	smoothing head
Engine Vibration	Isolated through rubber mounts
Seat	Premium UV protected, with adjustable
	armrests
Trailer	Integrated, extra heavy duty, folds from
	rolling position to transport position

Ground Pressure (Footprint)	3.8 psi (26 kPa)
Smoothing Heads	2 overlapping, fitted with tri-rollers in each head, no gap between heads
Rolling Width (Swath)	50" (1270mm)
Weight	726lb (330kg)
Drawbar	
Lifting weight when connecting	25lb (11kg)
Pin style, standard	Quick release, pin built in
Tires	18 x 6.50 x 8. 4 ply
Engine Start/Stop	Recoil & Switch
Brake	
Roller	Hydrostatic
Park	Handbrake, Drum style
OPS Seat Safety Switch	Operated through operator seat presence or absence
Optional Equipment	
Lights	ac/dc LED
Slicer - Quick release	15 blades, self-rotating on shaft & bearings
	Slice depth up to 30mm, (1 1/4")
Spiker - Quick release	30 wheels, self-rotating on SS shaft &
	bearings
	Spike depth 25mm, (1")
Brush - Quick release	Stiff or Medium strength bristles available
Drawbar coupling 2" (50mm)	Ball style
Drop down leg	Suits Ball style drawbar only
Warranty	2 years - Limited manufacturer's warranty.

